Technical datasheet

Agrolys BL100 #25/12,5

Agrotextiles - PP Woven groundcovers



Technical Textiles

Functions

Stimulates the growth of the plants
Prevents the growth of weeds
Not harmful to the environment and prevents the use of herbicides

Product Specifications

PROPERTIES	TEST METHOD	VALUE		UNIT	TOLERANCE
		WARP	WEFT		
MATERIAL		PP	PP		
TISSUE COLOUR		black			
PATTERN		rectangle 9.8/4.9 in			
		rectangle 25/12.5 cm			
COLOUR LINING		blue	red		
TISSUE WEIGHT	ASTM D5261	2.95		oz/y²	± 5 %
		100		g/m²	± 5 %
WIDTH		10.83 - 13.62 - 16.88		ft	± 0.1 ft
		330 - 415 - 515		cm	± 2 cm
LENGTH		328 100		ft	± 2%
				m	± 2 %

Technical characteristics

PROPERTIES	TEST METHOD	VALUE		UNIT	TOLERANCE
		WARP	WEFT		
TRAPEZOÏD TEAR STRENGTH	ASTM D4533	65	57	lbs	± 20 %
		0.29	0.25	kN	± 20 %
GRAB TENSILE STRENGTH	ASTM D4632	148	92	lbs	± 20 %
GRAB TENSILE STRENGTH		0.66	0.41	kN	± 20 %
GRAB ELONGATION	ASTM D4632	23.3	17.9	%	± 20 %
SHRINKAGE	15' à 70 °C	1.0	1.0	%	MAX
MULLEN BURST	ASTM D3768	237		psi	± 20%
		1635		kPa	± 20%

This information contained in this document is based on testing carried out by our laboratory or external research institutes and literature data, and based on Mean Values. This TDS is valid until further notice. To the best of our knowledge and at the time of publication, this information is true and accurate. It shall however, in no event be held to constitute or imply warranty undertaking express or implied commitment from the part of Beaulieu International Group – Division Beaulieu Technical Textiles. No liability whatever can be accepted by Beaulieu International Group – Division Beaulieu Technical Textiles with regard to the handling, processing or use of the product concerned which must in all cases be used in accordance with all applicable laws and regulations. The mentioned characteristics are not valid when the fabric has been in contact with sulphur-, chlorine-, iron- and brominederivates, as well as with copper sulphates and if the product is not installed and used in strict accordance with the installation instructions.

Technical Datasheet 608 : version 9 - ASTM Date : 20/05/2021